



AOPEN

Bright Ideas Connected

eTILE-X



10" IPC grade All-in-One for Industrial Self-service Kiosk eTILE-X10-FP


The AOPEN eTILE-X10-FP is an all-in-one display which is designed for factory automation and is applicable in kiosk solutions. It's designed for 24/7 consistent and reliable performance. AOPEN's slim miniITX motherboard runs a 2.3 GHz J3455 Quad Core, which is passively cooled by the AOPEN fanless thermal technology. The metal chassis and front bezel are IP65 rated, dust- and waterproof and the device passed the IK08 Impact test. This versatile model features 4 USB ports, 1 COM RS232 port, 1 LAN port, and dual display possibilities because of an extra HDMI output.

The eTILE-X10-FP features:

- + Industrial PCT touch solution with 5 touch points
- + Supports customised virtual key (up to 5 keys)
- + Wide range operating temperature: 0°C ~ 50°C
- + Supports PoE 802.3at
- + Mosh 5, 9H hardness glass
- + IP65 Grade front and IK08 protection



eTILE-X10-FP



Model name		eTILE-X10-FP	
Housing Material		Metal	
Dimension	W x H x D (mm)	306 x 206 x 33.3 mm	
	W x H x D (inch)	12.04 x 8.11 x 1.31 inch	
Weight		2.53kg / 5.58Pound	
CPU		Supports Intel® Apollo-Lake CPU Default configuration J3455	
Chipset		CPU Built-in	
Memory	Channel	Default 4G	
	Type	DDR3L SO-DIMM x 2	
	Data rate	1333 MHz	
	Max Memory	8GB	
Graphics		Integrated Intel® CPU	
Front Panel	Resolution	10.1" 1280 x 800 (16:9)	
	Max Brightness	400 nits	
	Panel Type	Vertical Alignment	
	View Angle(CR>10)	85/85/85/85	
	Response time	30ms	
	Contrast Ratio	900:1	
Touch		PCT support 5 points	
Expansion Slot		M.2 x 3	
Audio	Type	Realtek HD Audio Codec ALC269	
	Channel	2 Channel	
LAN	Realtek RTL8111H		
	10/100/1000		
Storage		M.2 SSD (Default 64GB)	
Security		Kensington Lock Hole	
TPM		2.0	
Storage Bay		-	
Front Camera		-	
Side Panel I/O	Power Button		-
	Brightness Up		-
	Brightness Down		-
	HDD Indicator		-
System I/O	DC Jack		x 1
	HDMI Out Port		x 1
	USB 2.0 Port		-
	USB 3.0 Port		x 4
	RJ45 LAN Jack		x 1
	Audio Set	Line-out	x 1
		Mic-in	x 1
	Extend power switch		x 1
Others		Embedded Antenna	
WatchDog Timer		1 ~ 255 SEC./ min	
IP Grade		IP65, IK08	
Adapter		POE 802.3at (optional SKU 90W, 19V, 4.74A, AC Adapter)	
Input Voltage		AC 100 ~ 240V	
Warranty		3 years	
Environment			
MTBF		50,000hrs	
Operating Temperature		0 ~50°C (32 ~ 122°F)	
Storage Temperature		-20 ~ 60°C (-4 ~ 140°F)	
Relative Humidity		90% RH (40°C non-Condensing)	

