



## Digital Engine Medically certified DE7600-M

The DE7600-M is a Digital Engine with all the necessary medical certifications to use its 24/7 operability in healthcare. The medical certifications make this device perfect for home healthcare environments and are used in patient monitors and patient ventilators.<sup>1</sup> The device has good operating temperatures and has no restricted materials present, such as lead, mercury or cadmium.<sup>2</sup> On top of that it withstands electromagnetic interference, compliant with medical regulations.<sup>3</sup> In short: a super safe mini PC, used in hospitals in patient rooms and other home healthcare applications!

The DE7600-M features:


- + 8th Generation Intel® Core™, available in i5 and i7
- + Medical grade AC adapter
- + HEVC/H.265 & VP9 high-definition playback (hardware accelerated)
- + Compact size
- + TPM2.0

<sup>1</sup> [https://www.aopengroup.com/en\\_GB/medical-devices/our-services/en\\_60601/](https://www.aopengroup.com/en_GB/medical-devices/our-services/en_60601/)

<sup>2</sup> [https://certifications.thomsonet.com/certifications/gi/osea/other-certification\\_registration/european-commission/ohs-compliant/](https://certifications.thomsonet.com/certifications/gi/osea/other-certification_registration/european-commission/ohs-compliant/)

<sup>3</sup> <https://www.3mest.co.uk/facts>

# DE7600-M



Model name		DE7600-M
Summary		Digital Engine for medical purposes.
Dimension	W x H x D (mm)	166 x 48 x 177 mm
	W x H x D (inch)	6.54 x 1.89 x 6.97 inch
Volume		1.41L
Weight		1.74 kgs
CPU		8th Generation Intel® Core™ (i5, i7)
Memory	Channel	Dual Channel
	Type	DDR4 SO-DIMM x 2
	Data rate	2666
	Max Memory	32G (based on OS Support)
Graphics	Chip	Intel® UHD Graphics 630
Expansion Slot		M.2 2242 x 1, M.2 2280 x 1, M.2 2230 x 1
Audio	Type	Realtek HD Audio ALC269Q
	Channel	Stereo
LAN		Realtek Gigabit Ethernet i210AT x 1, i219LM x 1 10 / 100 / 1000 Mbps
Storage	2.5" SATA HDD	-
	M.2 SSD	x 1
TPM		2.0

Supports:



Front Panel IO	USB 2.0 Port	-	
	USB 3.0 Port	-	
	Others	USB3.0 x 2	
Rear Panel IO	DC Jack	x 1 (12V / 19V)	
	HDMI Port	x 3 (HDMI2.0)	
	USB 2.0 Port	-	
	USB 3.0 Port	x 4	
	eSATA Port	-	
	RJ45 LAN Jack	x 2	
	Display Port	-	
	Audio Set	Line-Out	x 1
		Mic-in	x 1
	Antenna Holes	x 2	
	Kensington Lock Hole	x 1	
	COM Port	x 1	
	Others	-	
CPU Thermal Module		AOPEN Thermal Module	
WatchDog Timer		1 ~ 255 sec/min	
Adapter		GSM90A19-P1M (19V / 4.74A / 90W)	
Input Voltage		C 100 ~ 240V	
Warranty		2 Years	
Certifications		IEC 60601-1, EN 60601-1, CE, FCC, ROHS Compliance	
Environment			
MTBF		50,000 hrs	
Operating Temperature		0 ~ 50°C (32 ~ 122°F)	
Storage Temperature		-30 ~ 60°C (-22 ~ 140°F)	
Relative Humidity		95% RH (50° non-condensing)	

The specifications depicted may be subject to change without prior notice. All trademarks are copyright of their respective owners. © AOPEN Inc.